## Key **Features**

10-Point Multi-Touch | SuperClear® IPS Panel Technology | Ergonomic Dual-Hinge Design | Optimized Stylus Pen | Loaded With Connectivity

## Product **Description**

With responsive, in-cell touch technology and an advanced ergonomic design, the ViewSonic® TD2455 touch display delivers hands-on control for more productive workspaces and collaborative classrooms. This 24" (23.8" viewable) Full HD display features a SuperClear® IPS panel and a three-sided ultra-thin bezel design that lets you see more and do more with incredible images and expansive screen real estate. An intuitive 10-point Projected Capacitive (PCAP) touch screen delivers a smooth and responsive experience with every tap, pinch, and swipe. Its advanced ergonomic design delivers versatility and comfort for office use, check-in applications, and more. With DisplayPort out connectivity, the TD2455 easily connects to a projector or interactive whiteboard, making it ideal for use as a podium touch display option in classrooms and lecture halls. An included stylus pen lets you write or draw on screen, and easily attaches to the magnetic base of the display stand for secure storage and quick access. The stand also features an integrated client mount* for quick installation of VDI client endpoints on the back of the screen. So whether used on its own on office desktops, as a collaboration station in corporate huddle spaces, or as a front-of-classroom interactive teaching hub, the TD2455 helps to boost efficiency and productivity. *Client Mount Kit sold separately

1. VESA Compatible Wall Mount
2. Internal Speakers
3. AC In
4. HDMI 1.4
5. Display Port In
6. USB 3.2 Type A (x2)
7. Kensington Lock Slot
8. USB 3.2 Type B
9. Audio Out
10. Display Port Out
11. USB 3.2 Type C

24"
**DISPLAY**

IPS
**PANEL**

1920 x 1080
**RESOLUTION**

**Contact Sales**

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

### Display:

| | |
|---|---|
| Display Size (in.): | 24 |
| Viewable Area (in.): | 23.8 |
| Panel Type: | IPS |
| Resolution: | 1920 x 1080 |
| Resolution Type: | HD (1920x1080) |
| Static Contrast Ratio: | 1,000:1 |
| Dynamic Contrast Ratio: | 50,000,000:1 |
| Light Source: | LED |
| Brightness: | 250 cd/m2 |
| Colors: | 16.7M |
| Color Space Support: | 6 bit + Hi-FRC |
| Aspect Ratio: | 16:9 |
| Response Time (Typical GTG): | 14ms |
| Response Time (GTG w/OD): | 6ms |
| Viewing Angles: | 178º horizontal, 178º vertical |
| Backlight Life (Hours): | 30,000 |
| Panel Surface: | Anti-Glare type, Hard-coating (3H), Haze 25% |
| Refresh Rate (Hz): | 60 |

### Compatibility:

| | |
|---|---|
| PC Resolution (max): | 1920x1080 |
| Mac® Resolution (max): | 1920x1080 |

### Connector:

USB 3.2 Gen 1 Type A(2), USB 3.2 Gen 1 Type B(1), USB 3.2 Gen 1 Type C(1), HDMI 1.4 In(1), Display Port(1), Display Port Out(1)

### Touch:

| | |
|---|---|
| Touch Technology: | Projective Capacitive |
| Touch Points: | 10-Point Touch |
| Touch Compatibility: | Supports Windows 7/8/10, Linux Kernel Ubuntu 18.04/19.04, and Chromebox |

### Audio:

| | |
|---|---|
| Internal Speakers: | 2W (x2) |

### Power:

| | |
|---|---|
| Eco Mode (Conserve): | 11.3 |
| Eco Mode (optimized): | 14.5 |
| Consumption (typical): | 19.6 |
| Consumption (max): | 23.6 |
| Voltage: | AC 100-240V (universal), 50-60Hz |
| Stand-by: | 0.3W |
| Power Supply: | Internal |

### Additional Hardware:

| | |
|---|---|
| Kensington Lock Slot: | 1 |

### Controls:

| | |
|---|---|
| Physical Controls: | 1,2,3,4,5,6 [Power] |
| On Screen Display: | Auto image adjust, Contrast/Brightness, Input Select, Audio adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall |

### Operating Conditions:

| | |
|---|---|
| Temperature: | 32-104º F (0 - 40º C) |
| Humidity (non-condensing): | 20-90% |

### Mount:

| | |
|---|---|
| VESA Compatible: | 100 x 100 mm |

### Video Signal:

| | |
|---|---|
| Frequency Horizontal: | 15 ~ 82KHz |
| Frequency Vertical: | 50 ~ 75Hz |

### Video Input:

| | |
|---|---|
| Digital Sync: | TMDS for HDMI (v1.4), Micro-Packet for DisplayPort (v1.2), and USB Type C |

### Ergonomics:

| | |
|---|---|
| Tilt (Forward/Back): | 5º / 60º |

### Weight (imperial):

| | |
|---|---|
| Net (lbs): | 14.2 |
| Net Without Stand (lbs): | 8.2 |
| Gross (lbs): | 18.6 |

### Weight (metric):

| | |
|---|---|
| Net (kg): | 6.4 |
| Net Without Stand (kg): | 3.7 |
| Gross (kg): | 8.4 |

### Dimensions (imperial) (WxHxD):

| | |
|---|---|
| Packaging (in.): | 24.3 x 16.3 x 11.2 |
| Physical (in.): | 21.2 x 16.8 x 11.3 |
| Physical Without Stand (in.): | 21.2 x 12.6 x 2.0 |

### Dimensions (metric) (WxHxD):

| | |
|---|---|
| Packaging (mm): | 617.0 x 415.0 x 285.0 |
| Physical (mm): | 539.0 x 426.0 x 286.0 |
| Physical Without Stand (mm): | 539.0 x 320.0 x 52.0 |

### General:

Regulations: cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy

PACKAGE CONTENTS: TD2455 Display, Power Cable, DP Cable, USB 3.2 Cable, Passive Touch Pen, Passive Touch Pen Head, Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907004960

### Accessories:

CB-00008948, CB-00009950, CB-00010555, CB-00010684, CB-00010958, CB-00012984, LCD-CABLE-001, LCD-DMA-001, LCD-DMA-002, LCD-WMK-001, PG707W, PG707X, cb-00011486

### Awards:

Copyright © ViewSonic Corporation 2000-2020. All rights reserved. (08/28/2020 01:49 PM PST)